

BUTYL BOND PRO™

FOR A LONG-LASTING, WATER-TIGHT, & FLEXIBLE SEAL IN THE TOUGHEST ENVIRONMENTS.

Butyl Bond Pro is a high-performance sealant tape engineered to deliver a permanent moisture and vapor barrier across a wide variety of construction and industrial applications. Made with 100% solids, this tape stays flexible, non-sagging, and effective across extreme temperatures, ideal for professionals who demand reliability on every job.

FEATURES:

- Superior Adhesion to metal, wood, concrete, aluminum, plastics, and more
- Non-Corrosive and compatible with metals like Kynar 500, Zincalume, Galvalume, and galvanized steel
- No Sagging – even in vertical or overhead applications
- Permanently Flexible with 600–700% elongation
- Non-Staining, Minimal Odor, and Paintable with latex and enamel
- Safe & Compliant – Low VOC, USDA and FDA approved for incidental food contact
- 100% Solids Formula for long-term sealing strength
- Made in the USA

APPLICATIONS:

- Roofing & Metal Buildings
- HVAC & Refrigeration
- Concrete & Architectural Metals
- Plumbing, RV, and Manufactured Housing

INSTALLATION:

Apply to clean, dry surfaces. Firmly press tape into place before removing the release liner. For mechanical fastening, place tape on the side where fasteners will enter to ensure a secure seal between surfaces.

STORAGE:

- Store in a cool, dry place. Avoid excessive heat and keep away from oxidizers.
- Temperature Range: 10°F/-14°C to 100°F/38°C

SPECIFICATIONS:

- Color: Grey
- Tensile Strength: 22–25 PSI
- Service Temperature Range: -40°F to 249°F
- Shelf Life: 18–24 months
- Widths: 3/8", 3/4", & 1"
- Length: 45'
- 30 Rolls in a Box
- 32 Boxes on a Pallet



800-360-6467
MWICOMPONENTS.COM
©MWICOMPONENTS 2025